

## PITLOCK-Steckachsen / Thru axles



Made in Berlin since 1981

	Set 17	Set 17 boost	Set 18	Set 18 boost	Set 19	Set 20	Set 20 boost	Set 21	Set 21 boost	Set 22	Set 23	Set 23 kurz	Set 24	Set 24 boost	Set 25	Set 26	Set 26B	Set 26BL	Set 27	Set 29
<b>Artikelnummer</b> Article	P170000	P17B000	P180000	P18B000	P190000	P200000	P20B000	P210000	P21B000	P220000	P230000	P23K000	P240000	P24B000	P250000	P260000	P26B000	P26BL00	P270000	P290000
<b>Nachkauf (ohne Schlüssel)</b> reorder (without key)	PNC15ML	PNC15MB	PNC15FR	PNC15FB	PNC15ST	PNC12ML	PNC12MB	PNC15SU	PNC15SB	PNC15SK	PNC12MR	PNC12MRK	PNC12ET	PNC12EB	PNC15MC	PNC12XR	PNC12XB	PNC12XL	PNC12XF	PNC15SG
<b>Position</b> position	front	front	front	front	front	rear	rear	front	front	front	front	front	rear	rear	front	rear	rear	rear	front	front
<b>a</b> Durchmesser Diameter	15	15	15	15	15	12	12	15	15	15	12	12	12	12	15	12	12	12	12	15
<b>b</b> Gesamtlänge total length	148	158	146	156	133,2	174	179	140	150	118	125	120	170	175	125	162,5	170	175	120	141
<b>c</b> Einbaubreite installation width	100	110	100	110	100	142	148	100	110	100	100	100	142	148	100	142	142/148	148	100	100
<b>d</b> Gewindelänge thread length	20	20	15	20	15	20	20	/	/	/	20	20	20	20	15	20	20	20	20	20
<b>Gewinde</b> thread	M15 x 1,5	M15 x 1,5	M14 x 1,5	M14 x 1,5	M14 x 1,5	M12 x 1,75	M12 x 1,75	/	/	/	M12 x 1,5	M12 x 1,5	M12 x 1,5	M12 x 1,5	M15 x 1,5	M12 x 1,0	M12 x 1,0	M12 x 1,0	M12 x 1,0	M15 x 1,5
<b>Gewicht</b> weight	121/92g	129/100g	125/95g	131/100g	128/96g	114/80g	115/81g	152/122g	157/126g	140/110g	95/62g	92/61g	115/79g	116/80g	115/82g	109/77g	111/80g	113/82g	84/65g	84/65g
<b>Andruckfläche an Ausfallende</b> contact area on dropout	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 19 mm

